

TeloPTT TE300

ELEGANTLY SIMPLE, SUPERIOR AUDIO



TeloSystems
Bridging Communication Gap



Radio
Design
Interface



High-Capacity
Battery



Textured PTT
Button



Radio
Channel
Knob



Extremely
Loud Speaker



LTE/3G



3600mAh
Battery



GPS
Location



Android
OS



WiFi



Compact and
Handy

Dedicated Push-To-Talk Handheld

Instant communication to speed up the conversation.

Broadband connectivity to expand the worldwide coverage.

Specification

Items	Specifications
Frequency Band	<p>Global Version GSM: B5, B8, B3 CDMA: BC0 WCDMA: B1, B4, B5, B8 TDD-LTE: B40 FDD-LTE: B1, B3, B4, B5, B7, B8, B20, B28A, B28B</p> <p>American Version GSM: B5, B2 WCDMA: B1, B2, B4, B5 FDD-LTE: B1, B2, B4, B5, B7, B12, B17, B19, B25, B26, B28A, B28B</p>
WIFI	IEEE802.11 b/g/n (2.4G & 5G)
Bluetooth	Bluetooth 4.0 with BLE
GPS	GPS, GLONASS, AGPS
Optional Features	Gravity Sensor, NFC
Hardware	Specifications
CPU	MSM8909, 1.1GHz, Quad-Core
Memory	512M DDR3 + 4G ROM
Speaker	Ø36mm Max 2.0w
Battery	3600mAh
USB Port	USB 2.0 with Micro USB Type
Interface	M6 Interface for Remote Speaker Microphone, Earpiece
SIM Card Slot	Nano SIM Card
Software	Specifications
Operating System	Android 6.0
Physical	Specifications
Dimensions (H x W x D)	121.5*56.5*28.5mm
Weight	Less than 220g
Protection Rating	IP67
Working Temperature	-20°C ~ 60°C
Storage Temperature	-30°C ~ 70°C

Accessories



RSM-35



TSR1-290



TSR1-8800



MUC-300



TE300C1

Reliable & Flexible

6/F, No.42 Liuxian 1st Road, Bao'an District,
Shenzhen, China

Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telosystems.com

Web: www.telosystems.com