

ELEGANTLY SIMPLE, SUPERIOR AUDIO



TeloSystems
Bridging Communication Gap

Radio
Channel
Knob



Extremely
Loud Speaker



Textured PTT
Button



Radio
Design
Interface



TE300K



LTE/3G



3600mAh
Battery



GPS
Location



Android
OS



WiFi



Compact and
Handy

Dedicated Push-To-Talk Handheld

Instant communication to speed up the conversation.

Broadband connectivity to expand the worldwide coverage.

Specification

| Items | Specifications |
|------------------------|--|
| Frequency Band | Global Version GSM: B5, B8, B3 CDMA: BC0 WCDMA: B1, B4, B5, B8 TDD-LTE: B40 FDD-LTE: B1, B3, B4, B5, B7, B8, B20, B28A, B28B American Version GSM: B5, B2 WCDMA: B1, B2, B4, B5 FDD-LTE: B1, B2, B4, B5, B7, B12, B17, B19, B25, B26, B28A, B28B |
| WiFi | IEEE802.11 b/g/n (2.4G & 5G) |
| Bluetooth | Bluetooth 4.0 with BLE |
| GPS | GPS, GLONASS, AGPS |
| Optional Features | Gravity Sensor, NFC |
| Hardware | Specifications |
| CPU | MSM8909, 1.1GHz, Quad-Core |
| Memory | 512M DDR3 + 4G ROM |
| Display | 1.5" 128*64 LCD Non-touch Screen |
| Speaker | Ø36mm Max 2.0w |
| Battery | 3600mAh |
| USB Port | USB 2.0 with Micro USB Type |
| Interface | M6 Interface for Remote Speaker Microphone, Earpiece |
| SIM Card Slot | Nano SIM Card |
| Software | Specifications |
| Operating System | Android 6.0 |
| Physical | Specifications |
| Dimensions (H x W x D) | 121.5*56.5*28.5mm |
| Weight | Less than 220g |
| Protection Rating | IP67 |
| Working Temperature | -20°C ~ 60°C |
| Storage Temperature | -30°C ~ 70°C |

Accessories



RSM-35



TSR1-290



TSR1-8800



MUC-300



TE300C1

Reliable & Flexible

6/F, No.42 Liuxian 1st Road, Bao'an District,
Shenzhen, China

Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telox.com

Web: www.telox.com